



Automatic Electric Ltd.



INDOOR TAPE INSULATED RING TYPE "BPL" LOW TENSION CURRENT TRANSFORMER						
Ratio	Approximate Dimensions In mm			Burden (VA)	Accuracy Class	Price (Rs.)
	I.D. (A)	O.D. (B)	Ht. (C)			
50/5 A	30	80	50	5	5	400/-
60/5 A	30	80	50	5	5	400/-
75/5 A	30	80	50	5	5	400/-
100/5 A	30	80	50	5	1	400/-
100/5 A	30	80	95	15	1	1500/-
150/5 A	30	80	50	5	1	400/-
150/5 A	30	80	50	15	1	1300/-
200/5 A	50	95	40	10	1	400/-
200/5 A	50	95	40	15	1	800/-
250/5 A	50	95	40	10	1	450/-
250/5 A	50	95	40	15	1	800/-
300/5 A	50	95	40	10	1	500/-
300/5 A	50	95	40	15	1	700/-
400/5 A	60	100	35	15	1	400/-
500/5 A	60	100	35	15	1	400/-
600/5 A	60	100	35	15	1	400/-
800/5 A	80	125	35	15	1	500/-
1000/5A	80	125	35	15	1	550/-
1200/5 A	105	140	30	15	1	600/-
1500/5 A	115	150	30	15	1	800/-
1600/5 A	115	150	30	15	1	800/-
2000/5 A	115	150	30	15	1	900/-
2400/5 A	130	165	30	15	1	1000/-
2500/5 A	130	165	30	15	1	1000/-
3000/5 A	130	165	30	15	1	1100/-
3200/5 A	150	150	40	15	1	1400/-
4000/5 A	200	235	35	15	1	1900/-
5000/5 A	200	235	35	15	1	2500/-

Note :-

1. The accuracies listed above are as per I S S 2705/1992
2. 1 Amp Secondary at an extra cost of RS. 50/- upto 600/1A
3. 1 Amp Secondary at an extra cost of RS. 150/- above 600/1 A to 1600/1A
4. 1 Amp Secondary at an extra cost of RS. 250/- above 1600/1 A to 3200/1A
4. 1 Amp Secondary at an extra cost of RS. 500/- above 3200/1A