



POLYCAB INDIA LIMITED

Industrial Cables LP No. 03/2020-21 Dtd : 1st August 2020

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT LEAD FREE (FRLF) / HEAT RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FRLF	GREEN WIRES HR-FRLS-H-LF	FRLF BOX PACKING	GREEN WIRES HR-FRLS-H-LF BOX PACKING
	90 Mtrs.	90 Mtrs.	180 Mtrs.	180 Mtrs.
0.75	830	852		
1	1126	1155	2252	2310
1.5	1640	1685	3280	3370
2.5	2640	2710	5280	5420
4	3850	3955	7700	7910
6	5700	5855	11400	11710
10	9950	10220		
16	14705	15100		

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT LEAD FREE (FRLF) / HEAT RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE / FLAME RETARDANT LOW SMOKE (FRLS-H) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – HALOGEN FREE FLAME RETARDANT (HFFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FRLF POUCH PACKING	GREEN WIRES HR-FRLS-H-LF POUCH PACKING	FRLS-H POUCH PACKING	HFFR POUCH PACKING
	180 Mtrs.	180 Mtrs.	180 Mtrs.	180 Mtrs.
1	2025	2080	2053	2165
1.5	2938	3020	2980	3145
2.5	4812	4940	4880	5150
4	7378	7577	7450	7895
6	10879	11175	10990	11640

DATAR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT (FR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – HALOGEN FREE FLAME RETARDANT (HFFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)		HFFR
	90 Mtrs.	
0.75	804	892
1	1048	1210
1.5	1507	1763
2.5	2447	2838
4	3744	4139
6	5519	6128

Size wise Coils per Master Box as below

0.75	90 Mtrs.	28		
1	90 Mtrs.	24	180 Mtrs.	12
1.5	90 Mtrs.	16	180 Mtrs.	10
2.5	90 Mtrs.	12	180 Mtrs.	6
4	90 Mtrs.	8	180 Mtrs.	4
6	90 Mtrs.	6	180 Mtrs.	3
10	90 Mtrs.	1		
16	90 Mtrs.	1		

Notes

- The above rates are exclusive of GST which shall be charged extra.
- This Price List is subject to change without notice.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.



POLYCAB INDIA LIMITED

Industrial Cables LP No. 03/2020-21 Dtd : 1st August 2020

**POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES
FLAME RETARDANT LEAD FREE (FRLF) / FLAME RETARDANT LOW SMOKE (FRLSH) / HEAT
RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE CONFORMING TO IS-
694:2010 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE
GRADE 1100 VOLTS**

**POLYCAB PVC INSULATED SINGLE CORE
UNSHEATHED INDUSTRIAL(MULTISTRAND)
CABLES – HALOGEN FREE FLAME RETARDANT
(HFFR) WITH BRIGHT ANNEALED
ELECTROLYTIC BARE COPPER CONDUCTOR FOR
VOLTAGE GRADE 1100 VOLTS**

Size (sq.mm.)	FRLF	FRLS-H	GREEN WIRES HR-FRLS-H-LF	HFFR	Coils Per Box
	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	
0.75	2750	2785	2825	2940	10
1	3770	3820	3870	4035	8
1.5	5555	5630	5705	5945	6
2.5	9070	9200	9315	9705	4
4	8850	8940	9090	9470	4
6	13110	13240	13460	14030	3
10	24190	24430	24840	25880	1
16	37650	38030	38670	40280	1

Notes

1. The above rates are exclusive of GST which shall be charged extra.
2. This Price List is subject to change without notice.
3. As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.